

**ELASTOLLAN TPU  
NSF Potable Water Materials**

Trade Designation	End Use	Water Contact Temp	Water Contact Material
Elastollan 1154D13	A,P	CLD 23	PUR
Elastollan 1154D53	A,P	CLD 23	PUR
Elastollan 1164D5	A,P	CLD 23	PUR
Elastollan 1175D5	A,P	CLD 23	PUR
Elastollan 1180A10[2]	A	CLD 23	PUR
Elastollan 1180A10YU[2]	P	CLD 23	PUR
Elastollan 1180A50[2]	A	CLD 23	PUR
Elastollan 1180AFAH[2]	A	CLD 23	PUR
Elastollan 1185A10[2]	A	CLD 23	PUR
Elastollan 1185A10E20[2]	A	CLD 23	PUR
Elastollan 1185A10LC[2]	A	CLD 23	PUR
Elastollan 1185A10T[2]	A	CLD 23	PUR
Elastollan 1185A10U[2]	A	CLD 23	PUR
Elastollan 1185A10U Film[2]	A	CLD 23	PUR
Elastollan 1185A10V[2]	A	CLD 23	PUR
Elastollan 1185A10V Film	A	CLD 23	PUR
Elastollan 1185A10X[2]	A	CLD 23	PUR
Elastollan 1185A10XU[2]	A	CLD 23	PUR
Elastollan 1185A10Y[2]	A	CLD 23	PUR
Elastollan 1185A10YU[2]	A	CLD 23	PUR
Elastollan 1185A50E20[2]	A	CLD 23	PUR
Elastollan 1185A50V[2]	A	CLD 23	PUR
Elastollan 1190A10[3]	A	CLD 23	PUR
Elastollan 1190A10Y[3]	A	CLD 23	PUR
Elastollan 1190A10YU[2]	A	CLD 23	PUR
Elastollan 1190A16[3]	A	CLD 23	PUR
Elastollan 1190A50[3]	A	CLD 23	PUR
Elastollan 1190A50Y[3]	A	CLD 23	PUR
Elastollan 1190A55[3]	A	CLD 23	PUR
Elastollan 1195A10[4]	P	CLD 23	PUR
Elastollan 1195A10 Film[4]	P	CLD 23	PUR
Elastollan 1195A10FN[4]	P	CLD 23	PUR
Elastollan 1195A10R[4]	P	CLD 23	PUR
Elastollan 1195A50R[4]	P	CLD 23	PUR
Elastollan 1195A55[4]	P	CLD 23	PUR
Elastollan SP806-10[2]	A	CLD 23	PUR
Elastollan WY01585-1U[2]	A	CLD 23	PUR
Elastollan WY01585-5[2]	A	CLD 23	PUR
Elastollan WY05352D-1	A,P	CLD 23	PUR
Elastollan WY05352D-5	A,P	CLD 23	PUR
Elastollan WY08290-1[3]	A	CLD 23	PUR
Elastollan WY08290-5[3]	A	CLD 23	PUR
Elastollan WY08300-1FW	A,P	CLD 23	PUR
Elastollan® WY1140[1]	P	CLD 23	PUR
Elastollan® WY1141[1]	P	CLD 23	PUR

- [1] Certified for a maximum surface area to volume ratio of 310 sq. in./L.  
 [2] Certified for a maximum surface area to volume ratio of 200 sq. in./L.  
 [3] Certified for a maximum surface area to volume ratio of 250 sq. in./L.  
 [4] Certified for a maximum surface area to volume ratio of 500 sq. in./L.

A = Appurtenances other than pipe or fittings.  
 CLD 23 = Tested at 23 °C (73.4 °F)  
 P = Pipe  
 PUR = Polyurethane

NOTE: All Listed products from this facility are NSF Certified, whether or not they bear the NSF Mark.