

ELASTOLLAN TPU UL CERTIFICATIONS

Material Dsg	Color	Min. Thk (mm)	Flame Class	H W I	H A I	R T I			C T I
						Elec	Mech		
							Imp	Str	
Polyurethane (PUR), "Elastollan", furnished as granular material.									
11 75 A (a) W 000	NC	0.9-1.1 1.2 3	V-0 V-2 V-2	4 4 2	0 0 0	50 50 50	50 50 50	50 50 50	0
11 80 A (a) 000	NC	0.83	HB	-	-	50	50	50	
11 85 A (a)FHF 000	ALL	0.75 1.5 3	V-0 V-0 V-0	4 4 3	0 0 0	50 50 50	50 50 50	50 50 50	0
11 85 A (a)W 000	NC	0.75 1.5 3	V-2 V-2 V-2	- - -	- - -	50 50 50	50 50 50	50 50 50	
11 95 A (a) 000	ALL	0.75 3	HB HB	4 3	0 0	50 50	50 50	50 50	0
C 74D(a) 000	ALL	0.75 3	HB HB	4 3	0 0	50 50	50 50	50 50	0
C85 A (a) 000	ALL	0.9 3	HB HB	4 3	0 0	50 50	50 50	50 50	0
C98 A (a) 000	NC	1 3	HB HB	4 3	0 0	50 50	50 50	50 50	0
R3000	ALL	0.75 3	HB HB	- 4	- 0	50 50	50 50	50 50	0
S85 A (a) 000	NC	0.95	HB	-	-	50	50	50	
Polyurethane (PUR), "Elastollan", furnished as pellets.									
1185A-10	ALL	1.5	HB	-	-	50	50	50	
Polyurethane (PUR), "Elastollan".									
11 54 D(a) FHF 000	ALL	0.75 3	V-2 V-0	4 2	0 0	50 50	50 50	50 50	0
11 80 A (a) FHF 000	NC	1 3	V-2 V-0	- -	- -	50 50	50 50	50 50	
C 78 A (a)	ALL	0.9	HB	-	-	-	-	-	
C59 D(a) 000	ALL	0.75	HB	-	-	50	50	50	
R2000	ALL	1	HB	-	-	-	-	-	
Thermoplastic Polyurethane (TPU), "Elastollan", furnished as pellets.									
1185A10F 001 US (b)	WT	0.68	V-0	-	-	50	50	50	

(a) - Any two digit number, 00 to 99 inclusive, indicating shape of granulate and lubricant.

(b) - Oxygen Index is 32.8% maximum

Marking: Company name and material designation on container, wrapper or finished part.